



World's No.1
Air Treatment Company



FLOOR STANDING

FEATURES

2 / 4 Ton



Long Distance Wind Blast

The large air outlet and six large air directing blades enable an long distance airflow.




Touch Control

The control buttons are embedded into the body so that the unit can be controlled with only a gentle touch.



3D Airflow

Midea's 3D airflow function combines vertical and horizontal auto-swing to spread comfort more widely throughout the room.



Simple & Elegant Design

The modern and unique design of Midea's air conditioner delivers a premium look.



Easy Clean Filter

The air inlet grille and filter are easy to remove, making the cleaning process much easier.

TECHNICAL SPECIFICATION FOR XTREME SERIES NON INVERTER FLOOR STANDING AC

Model No			MFPA400 - 24ARN1	MFGA-48HRN1
Power supply		V-Hz-Ph	220-240V - 50Hz - 1Ph	380 - 415V - 50Hz - 3Ph
Cooling	Capacity	Btu/h	24000	48000
	Input	W	2700	5300
	Rated Current	A	13.04	9.1
	EER	W/W	2.62	2.67
Heating	Capacity	Btu/h	26000	52000
	Input	W	2500	5400
	Rated Current	A	12.08	9.2
	COP	W/W	3.07	2.84
Compressor Specification	Type		ROTARY	SCROLL
	Brand		GMCC	PANASONIC
	Input	W	2450	4750
	Refrigerant type	g	R 410A	R 410A
Refrigerant Piping	Liquid Side	mm (Inch)	9.52 (3/8)	12.7 (1/2)
	Gas Side	mm (Inch)	15.9 (5/8)	19 (3/4)
	Max.refrigerant pipe length	m	22	40
	Max. difference in level	m	12	25
Indoor Air Flow (Hi / Low)		m3/h	1154 / 980	1852 / 1562
Indoor Noise Level (Hi / Low)		dB(A)	47.5 / 40.5	55.5 / 50.3
Outdoor Noise Level		dB(A)	60	62.8
Indoor unit	Dimension(W x D x H)	mm	510 X 315 X 1750	550 X 350 X 1800
	Net Weight	kg	38.4	50
Outdoor unit	Dimension(W x D x H)	mm	845 X 363 X 702	900 X 350 X 1170
	Net Weight	kg	57.7	97

Note: The above mentioned specifications may change due to continuous R&D without prior notice.