



World's No.1
Air Treatment Company

Midea



WALL MOUNTED

FEATURES




Strong & Fast Cooling

Midea's distinctive 'Super Cool' function can instantly lower room temperature to 17°C in seconds.



Elegant Design

The streamlined exterior is pleasing to the eyes just like a soothing rhythm pleasing to the ear with air outlet and display screen ingeniously concealed.



Dual Protection

High Density Pre Filter collects dust and fungus. Micro Protection Filter along with Hepa Filter collects pollen, smoke, micro dust and bacteria.



Ultimate Comfort

With Follow Me Function, you can always enjoy the desired temperature wherever you stay in the room.



Leakage Detection

Indoor unit will show error code 'EC' and stop automatically when refrigerant leakage is detected. It protects compressor from being damaged.



Self Clean

Indoor unit will continue running at special combined mode to blow and dry indoor evaporator after the unit is switched off so as to keep clean and healthy.



Fire-Proof

Electronic Control Box adopts new design, which can meet higher fire safety requirement to prevent the internal fire due to electric spark accident.



Low Noise

It operates at a sound as low as 26db for your comfortable sleep.

TECHNICAL SPECIFICATION FOR XTREME SERIES NON INVERTER TYPE WALL MOUNTED AC

Model No			MSAGA-09HRN1	MSAGB-12HRN1	MSAGC-18HRN1	MSAGD-24HRN1
Power supply			V-Hz-Ph	220-240V - 50Hz - 1Ph	220-240V - 50Hz - 1Ph	220-240V - 50Hz - 1Ph
Cooling	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	776	1005	1557	2000
	Rated Current	A	3.4	4.5	6.7	8.8
	EER	W/W	3.42	3.52	3.41	3.54
Heating	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	690	929	1509	2015
	Rated Current	A	3	4.1	6.56	8.9
	COP	W/W	3.84	3.81	3.51	3.51
Compressor Specification	Type		ROTARY	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	GMCC	GMCC
	Input	W	660	845	1295	1610
	Refrigerant type	g	R 410A	R 410A	R 410A	R 410A
Refrigerant Piping	Liquid Side	mm (Inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	9.52 (3/8)
	Gas Side	mm (Inch)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)	15.9 (5/8)
	Max.refrigerant pipe length	m	15	15	15	15
	Max.difference in level	m	8	8	8	8
Indoor Air Flow (Hi / Med / Low)		m3/h	550 / 466 / 325	580 / 490 / 380	827 / 619 / 540	1121 / 997 / 911
Indoor Noise Level (Hi / Med / Low)		dB(A)	40 / 36 / 26	40 / 35 / 26	44 / 37 / 34	46 / 43 / 40
Outdoor Noise Level		dB(A)	54	55	57	60
Indoor unit	Dimension(W x D x H)	mm	729 / 200 / 292	802 / 200 / 295	971 / 228 / 321	1082 / 234 / 337
	Net Weight	kg	8.5	9.3	12.3	14.5
Outdoor unit	Dimension(W x D x H)	mm	720 / 270 / 495	720 / 270 / 495	805 / 330 / 554	890 / 342 / 673
	Net Weight	kg	27	29	39	50

Note: The above mentioned specifications may change due to continuous R&D without prior notice.